


Sechskant-Doppelnippel

nach DIN 2990

mit kegeligem Whitworth-Rohrgewinde nach DIN EN 10226

SF
GF-
107
R


PN	DN	R	B	L	GF-No.	€	GF-No.	€
50	6	1/8"	12	22	GF-10718-4i		GF-10718-7	
	8	1/4"	14	24	GF-10714-4i		GF-10714-7	
	10	3/8"	19	28	GF-10738-4i		GF-10738-7	
	15	1/2"	22	34	GF-10712-4i		GF-10712-7	
	20	3/4"	30	40	GF-10734-4i		GF-10734-7	
40	25	1"	36	46	GF-1071-4i		GF-1071-7	
	32	1 1/4"	46	52	GF-107114-4i		GF-107114-7	
	40	1 1/2"	50	54	GF-107112-4i		GF-107112-7	
	50	2"	65	62	GF-1072-4i		GF-1072-7	
	65	2 1/2"	80	70	GF-107212-4i		GF-107212-7	
25	80	3"	90	78	GF-1073-4i		GF-1073-7	
	100	4"	120	94	GF-1074-4i		GF-1074-7	

■ Werkstoff-Code:

1.4408~AISI 316-4i

1.4571-7

PN	DN	R	B	L	GF-No.	€
	6	1/8"	12	22	GF-10718-5i	
	8	1/4"	14	24	GF-10714-5i	
	10	3/8"	19	28	GF-10738-5i	
	15	1/2"	22	34	GF-10712-5i	
	20	3/4"	30	40	GF-10734-5i	
	25	1"	36	46	GF-1071-5i	
	32	1 1/4"	46	52	GF-107114-5i	
	40	1 1/2"	50	54	GF-107112-5i	
	50	2"	65	62	GF-1072-5i	
	65	2 1/2"	80	70	GF-107212-5i	
	80	3"	90	78	GF-1073-5i	
	100	4"	120	94	GF-1074-5i	

Zylindrische Gewinde
auf Anfrage.

■ Werkstoff-Code:

1.4408~AISI 316-5i
Drücke auf Anfrage.