


kwv

Kegel Winkel-Verschraubung

Passend in 24°-Konen (Bohrungsform W DIN 3861)


SF
DK-
264

	PN	∅ ≈ D M	S	B	A	l ₁	O-Ring	DK-No.	€
L	315	6 M 12 x 1,5	14	12	26,0	12,0	5,0 x 1,0	DK-2646LZ	
		8 M 14 x 1,5	17	12	27,5	14,0	6,0 x 1,5	DK-2648LZ	
		10 M 16 x 1,5	19	14	29,0	15,0	7,5 x 1,5	DK-26410LZ	
		12 M 18 x 1,5	22	17	29,5	17,0	9,0 x 1,5	DK-26412LZ	
		15 M 22 x 1,5	27	19	32,5	21,0	12,0 x 2,0	DK-26415LZ	
		18 M 26 x 1,5	32	24	35,5	23,5	15,0 x 2,0	DK-26418LZ	
	160	22 M 30 x 2,0	36	27	38,5	27,5	20,0 x 2,0	DK-26422LZ	
		28 M 36 x 2,0	41	36	41,5	30,5	26,0 x 2,0	DK-26428LZ	
		35 M 45 x 2,0	50	41	51,0	34,5	32,0 x 2,5	DK-26435LZ	
		42 M 52 x 2,0	60	50	56,0	40,0	38,0 x 2,5	DK-26442LZ	
S	630	6 M 14 x 1,5	17	12	27,0	16,0	5,0 x 1,0	DK-2646SZ	
		8 M 16 x 1,5	19	14	27,5	17,0	6,0 x 1,5	DK-2648SZ	
		10 M 18 x 1,5	22	17	30,0	17,5	7,5 x 1,5	DK-26410SZ	
		12 M 20 x 1,5	24	17	31,0	21,5	9,0 x 1,5	DK-26412SZ	
		14 M 22 x 1,5	27	19	35,0	22,0	10,0 x 2,0	DK-26414SZ	
		16 M 24 x 1,5	30	24	36,5	24,5	12,0 x 2,0	DK-26416SZ	
	400	20 M 30 x 2,0	36	27	44,5	26,5	16,3 x 2,4	DK-26420SZ	
		25 M 36 x 2,0	46	36	50,0	30,0	20,3 x 2,4	DK-26425SZ	
		30 M 42 x 2,0	50	41	55,0	35,5	25,3 x 2,4	DK-26430SZ	
		315 38 M 52 x 2,0	60	50	66,0	41,0	33,3 x 2,4	DK-26438SZ	

■ Werkstoff: 1.4571

O-Ring-Werkstoff: Viton

Auf Wunsch ohne Schneidring und Überwurfmutter lieferbar, in diesem Fall bitte „Z“ bei der DK-No. weglassen