



Verschraubung beidseitig Anschweissende

konisch dichtend



flach dichtend



SF
GF-144

Verschraubung konisch dichtend

PN	DN	Rohr	D x W	S	L	H	GF-No.	€
50	6	1/8"	10,2 x 2,00	19	35	15	GF-144C18-7	
	8	1/4"	13,5 x 2,35	27	35	15	GF-144C14-7	
	10	3/8"	17,2 x 2,35	27	40	16	GF-144C38-7	
	15	1/2"	21,3 x 2,65	32	48	16	GF-144C12-7	
	20	3/4"	26,9 x 2,65	41	55	18	GF-144C34-7	
40	25	1"	33,7 x 3,25	50	62	20	GF-144C1-7	
	32	1 1/4"	42,4 x 3,25	60	66	22	GF-144C114-7	
	40	1 1/2"	48,3 x 3,25	70	73	24	GF-144C112-7	
	50	2"	60,3 x 3,65	80	75	26	GF-144C2-7	
	65	2 1/2"	76,1 x 3,65	100	90	28	GF-144C212-7	
25	80	3"	88,9 x 4,05	110	100	30	GF-144C3-7	
	100	4"	114,3 x 4,50	135	105	31	GF-144C4-7	

■ Werkstoff: 1.4571

Verschraubung flach dichtend


PN	DN	Rohr	D x W	S	L	H	GF-No.	€
25	6	1/8"	10,2 x 2,00	19	35	15	GF-144F18-7	
	8	1/4"	13,5 x 2,35	27	35	15	GF-144F14-7	
	10	3/8"	17,2 x 2,35	27	40	16	GF-144F38-7	
	15	1/2"	21,3 x 2,65	32	48	16	GF-144F12-7	
	20	3/4"	26,9 x 2,65	41	55	18	GF-144F34-7	
16	25	1"	33,7 x 3,25	50	62	20	GF-144F1-7	
	32	1 1/4"	42,4 x 3,25	60	66	22	GF-144F114-7	
	40	1 1/2"	48,3 x 3,25	70	73	24	GF-144F112-7	
	50	2"	60,3 x 3,65	80	75	26	GF-144F2-7	
	65	2 1/2"	76,1 x 3,65	100	90	28	GF-144F212-7	
10	80	3"	88,9 x 4,05	110	100	30	GF-144F3-7	
	100	4"	114,3 x 4,50	135	105	31	GF-144F4-7	

■ Werkstoff: 1.4571

Flachdichtung aus PTFE
bei Temperaturen über 100°C Dichtungswerkstoff anfragen!

Verschraubung beidseitig Anschweissende

SF
GF-144



Verschraubung konisch dichtend

DN	Zoll	D	S	m	L	P	GF-No.	€	DN	Zoll	D	S	L	GF-No.	€
8	1/4"	13,5	21	13	39	14	GF-144C14-4L		8	1/4"	13,5	29	31,5	GF-144C14-5i	
10	3/8"	17,2	27	15	41	17	GF-144C38-4L		10	3/8"	17,2	34	34,5	GF-144C38-5i	
15	1/2"	21,3	32	16	45	22	GF-144C12-4L		15	1/2"	21,3	39	39,5	GF-144C12-5i	
20	3/4"	26,9	38	17,5	48	27	GF-144C34-4L		20	3/4"	26,9	47	44,5	GF-144C34-5i	
25	1"	33,7	46	18,5	50	35	GF-144C1-4L		25	1"	33,7	58	48,5	GF-144C1-5i	
32	1 1/4"	42,4	55	20	52	46	GF-144C114-4L		32	1 1/4"	42,4	67	55	GF-144C114-5i	
40	1 1/4"	48,3	63	21	55	53	GF-144C112-4L		40	1 1/4"	48,3	77	59	GF-144C112-5i	
50	2"	60,3	75	26	60	63	GF-144C2-4L		50	2"	60,3	90	63	GF-144C2-5i	

■ Werkstoff-Code: -4L = AISI 316L

-5i = 1.4408 ~AISI 316

Verschraubung flach dichtend

DN	Zoll	D	S	m	L	P	GF-No.	€	DN	Zoll	D	S	L	GF-No.	€
8	1/4"	13,5	21	13	39	14	GF-144F14-4L		8	1/4"	13,5	21	39	GF-144F14-5i	
10	3/8"	17,2	27	15	41	17	GF-144F38-4L		10	3/8"	17,2	27	41	GF-144F38-5i	
15	1/2"	21,3	32	16	45	22	GF-144F12-4L		15	1/2"	21,3	32	45	GF-144F12-5i	
20	3/4"	26,9	38	17,5	48	27	GF-144F34-4L		20	3/4"	26,9	38	48	GF-144F34-5i	
25	1"	33,7	46	18,5	50	35	GF-144F1-4L		25	1"	33,7	46	50	GF-144F1-5i	
32	1 1/4"	42,4	55	20	52	46	GF-144F114-4L		32	1 1/4"	42,4	55	52	GF-144F114-5i	
40	1 1/2"	48,3	63	21	55	53	GF-144F112-4L		40	1 1/2"	48,3	63	55	GF-144F112-5i	
50	2"	60,3	75	26	60	63	GF-144F2-4L		50	2"	60,3	75	60	GF-144F2-5i	

■ Werkstoff-Code: -4L = AISI 316L

-5i = 1.4408 ~AISI 316

Flachdichtung aus PTFE

bei Temperaturen über 100°C Dichtungswerkstoff anfragen!

1) = NPT mit anderen Maßen
Änderungen vorbehalten.